

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

- 1 1. (Currently Amended) A method for managing multiple resources in a system
2 including at least one host, network, and a storage space comprised of at least
3 one storage system that each host is capable of accessing over the network,
4 comprising:
5 measuring and monitoring a plurality of service level parameters indicating
6 a state of the resources in the system;
7 determining values for the service level parameters; determining whether
8 the service level parameter values satisfy predetermined service level thresholds;
9 indicating whether the service level parameter values satisfy the
10 predetermined service thresholds; and
11 determining a modification of one at least one resource deployment or
12 configuration if when the value for the service level parameter for the resource
13 does not satisfy the predetermined service level thresholds.
- 1 2. (Original) The method of claim 1, wherein the monitored service level parameter
2 comprises one of a performance parameter and an availability level of at least
3 one system resource.
- 1 3. (Currently Amended) The method of claim 2, wherein the service level
2 performance parameters that are monitored are members of a set of
3 performance parameters comprising: a downtime during which the at least one
4 application is unable to access the storage space; a number of times the at least
5 one application host was unable to access the storage space; a throughput in

6 terms of bytes per second transferred between the at least one host and the
7 storage; and an I/O transaction rate.

1 4. (Original) The method of claim 1, wherein the modification of resource
2 deployment comprises at least one of adding additional instances of the resource
3 and modifying a configuration of the resource.

1 5. (Currently Amended) The method of claim 1, wherein a time period is associated
2 with one of the monitored service parameters, further comprising: determining a
3 time during which the value of the service level parameter associated with the
4 time period does not satisfy the predetermined service level threshold; and
5 generating a message indicating that the determined time exceeds the time
6 period if when the determined time exceeds the time period associated with the
7 monitored service parameter.

1 6. (Original) The method of claim 5, wherein a customer contracts with a service
2 provider to provide the system at agreed upon service level parameters, further
3 comprising: transmitting a service message to the service provider after
4 determining that the value of the service level parameter does not satisfy the
5 predetermined service level; and transmitting the message indicating failure of
6 the value of the service level parameter for the time period to both the customer
7 and the service provider.

1 7. (Original) The method of claim 1, further comprising writing to a log information
2 indicating whether the service level parameter values satisfy the predetermined
3 service thresholds.

1 8. (Original) The method of claim 1, wherein determining the modification of the at
2 least one resource deployment further comprises: analyzing the resource
3 deployment to determine at least one resource that contributes to the failure of
4 the service level parameter values to satisfy the threshold; determining whether

- 5 any additional instances of the determined at least one resource that contributes
6 to the failure of the service level parameter is available; and allocating at least
7 one additional instance of the determined at least one resource to the system.
- 1 9. (Original) The method of claim 8, wherein analyzing the resource deployment
2 comprises performing a bottleneck analysis.
- 1 10. (Currently Amended) The method of claim 8, further comprising: determining
2 characteristics of access to the resources by applications operating at the service
3 level; if and when there are no additional instances of the determined at least one
4 resource, ~~then~~ determining whether the access characteristics exceed
5 predetermined access characteristics; and indicating that the service level is not
6 sufficient due to a change in the access characteristics.
- 1 11. (Original) The method of claim 10, wherein the access characteristics include
2 read/write ratio, Input/Output (I/O) size, and percentage of access being either
3 sequential or random.
- 1 12. (Original) The method of claim 10, wherein the predetermined access
2 characteristics are specified in a service level agreement that indicates the
3 thresholds for the service level parameter values.
- 1 13. (Original) The method of claim 1, wherein a plurality of applications at different
2 service levels are accessing the resources in the system, wherein requests from
3 applications using a higher priority service receive higher priority than requests
4 from applications operating at a lower priority service, wherein determining the
5 modification of the at least one resource deployment further comprises:
6 increasing the priority associated with the service level whose service level
7 parameter values fail to satisfy the predetermined service level thresholds.

- 1 14. (Currently Amended) The method of claim 13, wherein determining the
2 modification of the at least one resource deployment further comprises: analyzing
3 the resource deployment to determine at least one resource that contributes to
4 the failure of the service level parameter values to satisfy the thresholds;
5 determining whether any additional instances of the determined at least one
6 resource that contributes to the failure of the service level parameter is available;
7 and allocating at least one additional instance of the determined at least one
8 resource to the system, wherein the priority is increased if when there are no
9 additional instances of the at least one resource that contributes to the failure.
- 1 15. (Currently Amended) The method of claim 1, wherein one service level
2 parameter value indicates a time throughput of Input/Output operations between
3 the at least one host and the storage space has been below a throughput
4 threshold, and wherein determining the ~~additional resource allocation~~
5 modification of one at least one resource deployment or configuration further
6 comprises determining at least one of host adaptor, network, and storage
7 resources to add to the configuration.
- 1 16. (Currently Amended) The method of claim 1, further comprising: invoking an
2 operation to implement the determined ~~additional resource allocation~~ modification
3 of one at least one resource deployment or configuration.
- 1 17. (Currently Amended) The method of claim 1, wherein the service level
2 parameters specify a predetermined redundancy of resources, further
3 comprising: detecting a failure of one component; determining whether the
4 component failure causes the resource deployment to fall below the
5 predetermined redundancy ~~for~~ of resources; and indicating whether the
6 component failure causes the resource deployment to fall below the
7 predetermined redundancy threshold.

1 18. (Currently Amended) A system for managing multiple resources in a system
2 including at least one host, network, and a storage space comprised of at least
3 one storage system that each host is capable of accessing over the network,
4 comprising:
5 means for measuring and monitoring a plurality of service level
6 parameters indicating a state of the resources in the system;
7 means for determining values for the service level parameters; means for
8 determining whether the service level parameter values satisfy predetermined
9 service level thresholds;
10 means for indicating whether the service level parameter values satisfy
11 the predetermined service thresholds; and
12 means for determining a modification of at least one resource deployment
13 or configuration if when the value for the service level parameter for the resource
14 does not satisfy the predetermined service level thresholds.

1 19. (Currently Amended) The system of claim 18, wherein the service level
2 performance parameters that are monitored are members of a set of
3 performance parameters comprising: a downtime during which the at least one
4 application is unable to access the storage space; a number of times the at least
5 one application was unable to access the storage space; a throughput in terms of
6 bytes per second transferred between the at least one application and the
7 storage; and an I/O transaction rate.

1 20. (Original) The system of claim 18, wherein the modification of resource
2 deployment comprises at least one of adding additional instances of the resource
3 and modifying a configuration of the resource.

1 21. (Currently Amended) The system of claim 18, wherein a time period is
2 associated with one of the monitored service parameters, further comprising:
3 means for determining a time during which the value of the service level
4 parameter associated with the time period does not satisfy the predetermined

5 service level threshold; and means for generating a message indicating that the
6 determined time exceeds the time period if when the determined time exceeds
7 the time period associated with the monitored service parameter.

1 22. (Original) The system of claim 18, wherein the means for determining the
2 modification of the at least one resource deployment further performs: analyzing
3 the resource deployment to determine at least one resource that contributes to
4 the failure of the service level parameter values to satisfy the threshold;
5 determining whether any additional instances of the determined at least one
6 resource that contributes to the failure of the service level parameter is available;
7 and allocating at least one additional instance of the determined at least one
8 resource to the system.

1 23. (Currently Amended) The system of claim 22, further comprising: means for
2 determining characteristics of access to the resources by applications operating
3 at the service level; means for determining whether the access characteristics
4 exceed predetermined access characteristics if when there are no additional
5 instances of the determined at least one resource; and means for indicating that
6 the service level is not sufficient due to a change in the access characteristics.

1 24. (Original) The system of claim 18, wherein a plurality of applications at different
2 service levels are accessing the resources in the system, wherein requests from
3 applications using a higher priority service receive higher priority than requests
4 from applications using a lower priority service, wherein determining the
5 modification of the at least one resource deployment further comprises:
6 increasing the priority associated with the service level whose service level
7 parameter values fail to satisfy the predetermined service level thresholds.

1 25. (Currently Amended) A system for managing multiple resources in a system
2 including at least one host, network, and a storage space comprised of at least

3 one storage system that each host is capable of accessing over the network,
4 comprising:
5 a processing unit;
6 a computer readable medium accessible to the processing unit;
7 program code embedded in the computer readable medium executed by
8 the processing unit to perform:
9 (i) measuring and monitoring a plurality of service level parameters
10 indicating a state of the resources in the system;
11 (ii) determining values for the service level parameters;
12 (iii) determining whether the service level parameter values satisfy
13 predetermined service level thresholds;
14 (iv) indicating whether the service level parameter values satisfy the
15 predetermined service thresholds; and
16 (v) determining a modification of at least one resource deployment or
17 configuration if when the value for the service level parameter for
18 the resource does not satisfy the predetermined service level
19 thresholds.

1 26. (Currently Amended) The system of claim 25, wherein the service level
2 performance parameters that are monitored are members of a set of
3 performance parameters comprising: a downtime during which the at least one
4 application is unable to access the storage space; a number of times the at least
5 one application was unable to access the storage space; a throughput in terms of
6 bytes per second transferred between the at least one application and the
7 storage; and an I/O transaction rate.

1 27. (Original) The system of claim 25, wherein the program code for determining the
2 modification of the resource deployment comprises at least one of adding
3 additional instances of the resource and modifying a configuration of the
4 resource.

- 1 28. (Currently Amended) The system of claim 25, wherein a time period is
2 associated with one of the monitored service parameters, wherein the program
3 code is further executed by the processing unit to perform: determining a time
4 during which the value of the service level parameter associated with the time
5 period does not satisfy the predetermined service level threshold; and generating
6 a message indicating that the determined time exceeds the time period if when
7 the determined time exceeds the time period associated with the monitored
8 service parameter.
- 1 29. (Original) The system of claim 25, wherein the program code for determining the
2 modification of the at least one resource deployment further causes the
3 processing unit to perform: analyzing the resource deployment to determine at
4 least one resource that contributes to the failure of the service level parameter
5 values to satisfy the threshold; determining whether any additional instances of
6 the determined at least one resource that contributes to the failure of the service
7 level parameter is available; and allocating at least one additional instance of the
8 determined at least one resource to the system.
- 1 30. (Currently Amended) The system of claim 29, wherein the program code is
2 further executed by the processing unit to perform: determining characteristics of
3 access to the resources by applications operating at the service level;
4 determining whether the access characteristics exceed predetermined access
5 characteristics if when there are no additional instances of the determined at
6 least one resource; and indicating that the service level is not sufficient due to a
7 change in the access characteristics.
- 1 31. (Original) The system of claim 25, wherein a plurality of applications at different
2 service levels are accessing the resources in the system, wherein requests from
3 applications using a higher priority service receive higher priority than requests
4 from applications using a lower priority service, wherein the program code for
5 determining the modification of the at least one resource deployment further

causes the processing unit to perform: increasing the priority associated with the service level whose service level parameter values fail to satisfy the predetermined service level thresholds.

32. (Currently Amended) An article of manufacture including code for managing multiple resources in a system including at least one host, network, and a storage space comprised of at least one storage system that each host is capable of accessing over the network, wherein the code is capable of causing operations comprising:
- measuring and monitoring a plurality of service level parameters indicating a state of the resources in the system;
 - determining values for the service level parameters;
 - determining whether the service level parameter values satisfy predetermined service level thresholds; indicating whether the service level parameter values satisfy the predetermined service thresholds; and
 - determining a modification of one at least one resource deployment or configuration if when the value for the service level parameter for the resource does not satisfy the predetermined service level thresholds.

33. (Original) The article of manufacture of claim 32, wherein the monitored service level parameter comprises one of a performance parameter and an availability level of at least one system resource.

34. (Original) The article of manufacture of claim 33, wherein the service level performance parameters that are monitored are members of a set of performance parameters comprising: a downtime during which the at least one host is unable to access the storage space; a number of times the at least one host was unable to access the storage space; a throughput in terms of bytes per second transferred between the at least one host and the storage; and an I/O transaction rate.

- 1 35. (Original) The article of manufacture of claim 32, wherein the modification of
2 resource deployment comprises at least one of adding additional instances of the
3 resource and modifying a configuration of the resource.
- 1 36. (Currently Amended) The article of manufacture of claim 32, wherein a time
2 period is associated with one of the monitored service parameters, further
3 comprising: determining a time during which the value of the service level
4 parameter associated with the time period does not satisfy the predetermined
5 service level threshold; and generating a message indicating that the determined
6 time exceeds the time period if when the determined time exceeds the time
7 period associated with the monitored service parameter.
- 1 37. (Original) The article of manufacture of claim 36, wherein a customer contracts
2 with a service provider to provide the system at agreed upon service level
3 parameters, further comprising: transmitting a service message to the service
4 provider after determining that the value of the service level parameter does not
5 satisfy the predetermined service level; and transmitting the message indicating
6 failure of the value of the service level parameter for the time period to both the
7 customer and the service provider.
- 1 38. (Original) The article of manufacture of claim 32, further comprising writing to a
2 log information indicating whether the service level parameter values satisfy the
3 predetermined service thresholds.
- 1 39. (Original) The article of manufacture of claim 32, wherein determining the
2 modification of the at least one resource deployment further comprises: analyzing
3 the resource deployment to determine at least one resource that contributes to
4 the failure of the service level parameter values to satisfy the threshold;
5 determining whether any additional instances of the determined at least one
6 resource that contributes to the failure of the service level parameter is available;

7 and allocating at least one additional instance of the determined at least one
8 resource to the system.

1 40. (Original) The article of manufacture of claim 39, wherein analyzing the resource
2 deployment comprises performing a bottleneck analysis.

1 41. (Currently Amended) The article of manufacture of claim 39, further comprising:
2 determining characteristics of access to the resources by applications operating
3 at the service level; if and when there are no additional instances of the
4 determined at least one resource, ~~then~~ determining whether the access
5 characteristics exceed predetermined access characteristics; and indicating that
6 the service level is not sufficient due to a change in the access characteristics.

1 42. (Original) The article of manufacture of claim 41, wherein the access
2 characteristics include read/write ratio, Input/Output (I/O) size, and a percentage
3 of access being either sequential or random.

1 43. (Original) The article of manufacture of claim 41, wherein the predetermined
2 access characteristics are specified in a service level agreement that indicates
3 the thresholds for the service level parameter values.

1 44. (Original) The article of manufacture of claim 32, wherein a plurality of
2 applications at different service levels are accessing the resources in the system,
3 wherein requests from applications using a higher priority service receive higher
4 priority than requests from applications operating at a lower priority service,
5 wherein determining the modification of the at least one resource deployment
6 further comprises: increasing the priority associated with the service level whose
7 service level parameter values fail to satisfy the predetermined service level
8 thresholds.

1 45. (Currently Amended) The article of manufacture of claim 44, wherein determining
2 the modification of the at least one resource deployment further comprises:
3 analyzing the resource deployment to determine at least one resource that
4 contributes to the failure of the service level parameter values to satisfy the
5 thresholds; determining whether any additional instances of the determined at
6 least one resource that contributes to the failure of the service level parameter is
7 available; and allocating at least one additional instance of the determined at
8 least one resource to the system, wherein the priority is increased if when there
9 are no additional instances of the at least one resource that contributes to the
10 failure.

1 46. (Currently Amended) The article of manufacture of claim 32, wherein one service
2 level parameter value indicates a time throughput of Input/Output operations
3 between the at least one host and the storage space has been below a
4 throughput threshold, and wherein determining the additional resource allocation
5 modification of one at least one resource deployment or configuration further
6 comprises determining at least one of host adaptor, network, and storage
7 resources to add to the configuration.

1 47. (Currently Amended) The article of manufacture of claim 32, further comprising:
2 invoking an operation to implement the determined additional resource allocation
3 modification of one at least one resource deployment or configuration.

1 48. (Currently Amended) The article of manufacture of claim 32, wherein the service
2 level parameters specify a predetermined redundancy of resources, further
3 comprising: detecting a failure of one component; determining whether the
4 component failure causes the resource deployment to fall below the
5 predetermined redundancy ~~to~~ of resources; and indicating whether the
6 component failure causes the resource deployment to fall below the
7 predetermined redundancy threshold.